

POWERMAX 125

Especificación	Valor
Input voltages	120-240 V, 1-PH, 50/60 Hz
Input current @ 3.8 kW	120-240 V, 1-PH, 25-18.8 A
Output current	15-30 A
Rated output voltage	125 VDC
Duty cycle @ 40°C (104°F)	35%, 240 V 20%, 120 V
Open circuit voltage (OCV)	256 VDC
Dimensions with handles	356 mm (14.0") D; 168 mm (6.6") W; 305 mm (12.0") H
Weight w/ 4,5 m (15') torch	CSA: 9.7 kg (21.4 lbs) CE, CCC: 9.5 kg (21 lbs)
Gas Supply	Clean, dry, oil-free air or nitrogen
Recommended gas inlet flow rate / pressure	113.3 l/min (4 scfm) at 5.5 bar (80 psi)
Input power cable length	3 m (10')
Power supply type	Inverter - IGBT
Engine drive requirement	5.5 kW for full 30 A output
Certifications	CSA-certified for use in the Americas and Asia, except China CE, C-Tick, CU/GOST, Ukr, and Serbian — for use in Europe, Australia, Belarus, Kazakhstan, Russia, Serbia, Ukraine, and other countries where accepted. CCC for use in China.
Warranty	Power supplies have a 3-year warranty and torches a 1-year warranty.

Cotiza directo a nuestro correo (clic en el link):[mailto: contactenos@saltec-mexico.com.mx?subject=Cotización](mailto:contactenos@saltec-mexico.com.mx?subject=Cotización)